15 Gallon Concentrate Foam Unit

FI-CN-15N



The Good Stuff

- **Easy to use, easy to maintain**
  Designed for portability, efficiency, and hassle-free maintenance. Our quick-change pump and tool-free, hinged access plate reduce downtime when a repair is needed
- **No manual mixing**
  Automatically dilutes chemistry on the go, saves time and labor
- **Configure with color**
  Lids and hoses come in a variety of colors to match your chemical management systems and quickly tell units apart in your chemical cage

Features

- Draws from concentrated product
- Powered by compressed air
- Dilutes at ratios of 14:1 to 320:1
- Holds two chemical jugs or one standard 5 gallon bucket (chemical jugs/bucket not included)
- On-board water tank – 15 gallon (56.8 liter) capacity
- Hinged back plate provides tool-free access to components
- Quick-change pump
- Hinged lid
- Anti-kink hose protection
- Natural color tank for easy visibility of water levels
- Integrated hose wraps
- Front-facing drain
- In-line strainer to protect pump from debris

Options

- Color coding
  - Lid – 9 colors (BK, BL, BN, GN, OR, PL, RD, WH, YL)
  - Discharge hose – 4 colors (BL, GN, YL, RD)

Industries

- Food and Beverage
- Manufacturing

How to Buy

Specs

- **Power type** ..... compressed air
- **Chemical pickup type** ..... draws from concentrated product
- **Dilution ratio range** ..... 14:1 to 320:1
- **Number of products unit can draw from** ..... one product
- **Suction line length/diameter** ..... 8 ft. (2.4 m) clear hose with 1/4 in. (6.4 mm) inside diameter
- **Capacity** ..... 15 gallons (56.8 liters) of water; up to 10 gallons (37.9 liters) of concentrate
- **Discharge line length/diameter** ..... 30 ft. (9 m) hose, with 3/4 in. (19 mm) inside diameter
- **Discharge wand/tip type** ..... 7 in. (17.8 cm) stainless steel wand with zero tip and ball valve
- **Output distance** ..... 25-30 ft. (7.6-9.1 m)
- **Output volume** ..... 20-45 gal/min (75.7-170.3 l/min)
- **Flow rate** ..... 2 gal/min (7.6 l/min)
- **Pump seals** ..... Santoprene, Viton, or Kalrez
- **Wheel type** ..... two 10 inch (25.4 cm) non-marking wheels and two 5 inch (12.7 cm) casters, one with lock

Requirements

- **Compressed air requirements** ..... 40-80 psi (2.8-5.5 bar) with 5-10 CFM (141.6-283.2 l/min)
- **Liquid temperature range** ..... 40-100˚F (4.4-37.8˚C)
- **Chemical compatibility** ..... chemical products used with this equipment must be formulated for this type of application and compatible with unit materials and pump seals. For more information on chemical compatibility, consult the manufacturer or SDS for your product or contact our customer service department.