dual pumps



207PDY

757 Lpm	4 Bar	40m Head	Diesel Yanmar

Diesel

207PDY

757	4
Lpm	Bar

YANMAR



Pairing the class leading Pacer S Pump with the Yanmar 4.6hp L48N diesel engine gives an ideal combination to perform in any commercial or industrial application. The 2" pump is available with high flow or high pressure impeller with flows up to 871Lpm and pressures up to 4 Bar.



Yanmar L48N Engine

Pump	
Make	Pacer
Model	S Series - SE2UL
Max Flow	757 Lpm
Max Pressure	4 Bar
Body	Corrosion resistant polyester
Seals	EPDM (Buna & Viton available)
Mechanical seal	Carbon ceramic
Impeller	Polyester 706 - 5 vane
Inlet & Outlet	2" NPT female (BSP available)
Suction lift	Up to 7.6m
Notes	Self priming after initial prime

Engine	
Make	Yanmar
Model	L48N
Power	4.6Hp - Gross
Shaft	3/4" parallel keyway shaft
Fuel capacity	2.4 Litres
Lubrication	Oil splash
Oil sensor	Yes
Cooling	Air cooled
Fuel system	Direct injection
Starting	Recoil

Weight & Dimensions	
Weight	31.2 Kg
Dimensions	L532 - W384 - H417 mm

Dealer Stamp