
dual pumps


M500-1442



106 Lpm	200 Bar	400 Volt	60 Hp

M500-1442

106	200
Lpm	Bar



Motor	
Voltage	400 Volts - 50 Hz - 80.6 Amps
Power / FL Torque	60 Hp - 45 Kw - 438 Nm
Speed	980 Rpm - 6 pole
Efficiency	IE3
Protection	IP55
Thermal Protection	PTC 140°C
Frame	IEC 280S frame - B3 foot mount - B5 face
Material	Cast Iron

Pump	
Make	Pratissoli KF Series
Model	KF30
Flow	106 Lpm
Pressure	200 Bar - 2900 Psi
Max temp	40°C
Materials	Stainless steel manifold

Overall Weight & Dimensions
1700L x 775W x 750H (mm) - 790 kg

Drive & Mounting	
Motor Shaft	75mm male
Pump Shaft	40mm male
Mounting	Flexible drive coupling & flange

Port Sizes	
Filter inlet	2" hose barb
High pressure outlet	3/4" BSP male thread
Bypass	40mm hose barb

M500-1442 Principle Components



Pratissoli R2
Pressure Regulator



Pratissoli S723
Safety Valve



Pratissoli A7
Pulsation Dampener



2" Brass Y Type
Inlet Filter