QUALUBE ENDURASYN SS 10W30

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
Issue date: 21/03/2024 Revision date: 22/07/2024 Supersedes version of: 21/03/2024 Version: 1.1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form	:	Mixture
Trade name	:	QUALUBE ENDURASYN SS 10W30
UFI	:	3AT0-6086-G00P-JRMN
Product code	:	ENDUR10W30

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Main use category	:	Professional use,Industrial use
Use of the substance/mixture	:	Lubricants and additives

1.3. Details of the supplier of the safety data sheet

Witham Group
Outer Circle Road
LN2 4HL Lincoln, Lincolnshire
United Kingdom
T 01522 521192
ralph.godbold@withamgroup.co.uk, www.withamgroup.co.uk

1.4. Emergency telephone number

Emergency number	:	01522 521192 (Monday to Thursday 8.00-17.00, Friday 8.00-16.30)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Not classified

Adverse physicochemical, human health and environmental effects

Causes skin irritation. Causes serious eye irritation. May be fatal if swallowed and enters airways.

Blending Quality, Value & Service since 1921
Head Office
WITHAM OIL & PAINT (SOHAM) LTD
Regal Drive
Soham
Cambs CB7 5BE
01353 723373
WITHAM OIL & PAINT LTD
Outer Circle Road
Lincoln
LN2 4HL
01522 521192
WITHAM MOTORSPORT LTD
Regal Drive
Soham
Cambs CB7 5BE
01353 723373
withamgroup.co.uk
bsi ISO 9001 Quality Management Systems CERTIFIED FM37897 ISO 14001 Environmental Management CERTIFIED EMS727531
Qualube THE QUALITY LUBRICANT
Woco THE QUALITY PAINT
03/23

QUALUBE ENDURASYN SS 10W30

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

EUH-statements : EUH208 - Contains Benzenesulfonic acid methyl-,mono-C20-26-branched alkyl derivs, calcium salts (722503-69-7) (21139), Benzenesulfonic acid methyl1-,mono-C20-24-branched alkyl derivs,calcium salts (722503-68-6) (21138). May produce an allergic reaction.

2.3. Other hazards

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII
This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
Contains no PBT and/or vPvB substances ≥ 0.1% assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
DISTILLATES(PETROLEUM) HYDROTREATED HEAVY PARAFFINIC	CAS-No.: 64742-54-7 EC-No.: 265-157-1 EC Index-No.: 649-467-00-8	≥ 80 – < 90	Carc. 1B, H350
HIGHLY REFINED MINERAL OIL MIXTURE(C15-C50)	-	≥ 5 – < 10	Asp. Tox. 1, H304
Highly Refined mineral oil(C15-C50)	-	≥ 1 – < 5	Not classified
Phosphorodithioic acid, mixed O,O-bis(iso-bu and pentyl) esters, zinc salts	CAS-No.: 68784-31-6 EC-No.: 272-238-5	< 1	Eye Dam. 1, H318 Aquatic Chronic 2, H411
Benzenesulfonic acid methyl-,mono-C20-26-branched alkyl derivs., calcium salts	CAS-No.: 722503-69-7	< 1	Skin Sens. 1B, H317 Aquatic Chronic 4, H413
NON CLASSIFIED COMPONENT	-	< 1	Not classified

Blending Quality, Value & Service since 1921
Head Office
WITHAM OIL & PAINT (SOHAM) LTD
Regal Drive
Soham
Cambs CB7 5BE
01353 723373
WITHAM OIL & PAINT LTD
Outer Circle Road
Lincoln
LN2 4HL
01522 521192
WITHAM MOTORSPORT LTD
Regal Drive
Soham
Cambs CB7 5BE
01353 723373
withamgroup.co.uk
bsi ISO 9001 Quality Management Systems CERTIFIED FM37897 ISO 14001 Environmental Management CERTIFIED EMS727531
Qualube THE QUALITY LUBRICANT
Woco THE QUALITY PAINT
03/23

QUALUBE ENDURASYN SS 10W30

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Benzenesulfonic acid methyl1-,mono-C20-24-branched alkyl derivs.,calcium salts	CAS-No.: 722503-68-6	< 1	Skin Sens. 1B, H317 Aquatic Chronic 4, H413

Comments : The data shown are in accordance with the latest EC directives.
H350 Does not apply.
The mineral oils in the product contain <3% DMSO extract (IP 346)

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Get medical advice/attention if you feel unwell.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.

First-aid measures after skin contact : Wash skin with plenty of water. Take off contaminated clothing. If skin irritation occurs: Get medical advice/attention. If the product is injected into or under the skin, or into any part of the body, regardless of the appearance of the wound or its size, the individual should be evaluated immediately by a physcian as a surgical emergency. Even though initial symptoms from high pressure injection may be minimal or absent, early surgical treatment within the first few hours may significantly reduce the ultimate extent of injury.

First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

First-aid measures after ingestion : Do not induce vomiting. Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects : The severity of the symptoms described will vary dependent on the concentration and the length of exposure.

Symptoms/effects after inhalation : May cause headache, nausea and irritation of respiratory tract.

Symptoms/effects after skin contact : Irritation. Prolonged or repeated contact may cause skin to become dry. irritation (itching, redness, blistering).

Symptoms/effects after eye contact : Eye irritation.

Symptoms/effects after ingestion : Risk of lung oedema.

Blending Quality, Value & Service since 1921
Head Office
WITHAM OIL & PAINT (SOHAM) LTD
Regal Drive
Soham
Cambs CB7 5BE
01353 723373
WITHAM OIL & PAINT LTD
Outer Circle Road
Lincoln
LN2 4HL
01522 521192
WITHAM MOTORSPORT LTD
Regal Drive
Soham
Cambs CB7 5BE
01353 723373
withamgroup.co.uk
bsi ISO 9001 Quality Management Systems CERTIFIED FM37897 ISO 14001 Environmental Management CERTIFIED EMS727531
Qualube THE QUALITY LUBRICANT
Woco THE QUALITY PAINT
03/23

QUALUBE ENDURASYN SS 10W30

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	:	Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media	:	Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard	:	In case of fire and/or explosion do not breathe fumes.
Hazardous decomposition products in case of fire	:	Toxic fumes may be released. Carbon dioxide. Carbon monoxide.

5.3. Advice for firefighters

Precautionary measures fire	:	Evacuate area.
Firefighting instructions	:	Prevent fire fighting water from entering the environment. Use water spray or fog for cooling exposed containers. In case of fire: stop leak if safe to do so.
Protection during firefighting	:	Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. EN 469. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Wear protective clothing as described in Section 8 of this data sheet.

For non-emergency personnel

Protective equipment	:	Wear recommended personal protective equipment.
Emergency procedures	:	Ventilate spillage area. Avoid contact with skin and eyes.

For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

Blending Quality, Value & Service since 1921

Head Office

WITHAM OIL & PAINT (SOHAM) LTD
Regal Drive
Soham
Cambs CB7 5BE
01353 723373

WITHAM OIL & PAINT LTD
Outer Circle Road
Lincoln
LN2 4HL
01522 521192

WITHAM MOTORSPORT LTD
Regal Drive
Soham
Cambs CB7 5BE
01353 723373

withamgroup.co.uk

bsi ISO 9001 Quality Management Systems CERTIFIED FM37897 ISO 14001 Environmental Management CERTIFIED EMS727531

Qualube THE QUALITY LUBRICANT
Woco THE QUALITY PAINT

03/23

QUALUBE ENDURASYN SS 10W30

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

6.3. Methods and material for containment and cleaning up

Methods for cleaning up	:	Take up mechanically (sweeping, shovelling) and collect in suitable container for disposal. Small quantities of liquid spill: take up in non-combustible absorbent material and shovel into container for disposal. Take up liquid spill into absorbent material, e.g.: sand. This material and its container must be disposed of in a safe way, and as per local legislation.
Other information	:	Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13. For further information refer to section 8: "Exposure controls/personal protection".

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling	:	Ensure good ventilation of the work station. Avoid contact with skin and eyes. Wear personal protective equipment.
Hygiene measures	:	Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures	:	Keep in a cool, well-ventilated place away from heat.
Storage conditions	:	Store at temperatures not exceeding 25 deg c. Store in a well-ventilated place. Keep cool.
Incompatible products	:	Oxidizing agent.
Incompatible materials	:	Heat sources.

7.3. Specific end use(s)

The identified uses for this product are detailed in Section 1.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

National occupational exposure and biological limit values

Blending Quality, Value & Service since 1921

Head Office

WITHAM OIL & PAINT (SOHAM) LTD
Regal Drive
Soham
Cambs CB7 5BE
01353 723373

WITHAM OIL & PAINT LTD
Outer Circle Road
Lincoln
LN2 4HL
01522 521192

WITHAM MOTORSPORT LTD
Regal Drive
Soham
Cambs CB7 5BE
01353 723373

withamgroup.co.uk

bsi ISO 9001 Quality Management Systems CERTIFIED FM37897 ISO 14001 Environmental Management CERTIFIED EMS727531

Qualube THE QUALITY LUBRICANT
Woco THE QUALITY PAINT

03/23

QUALUBE ENDURASYN SS 10W30

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Highly Refined mineral oil(C15-C50)	
United Kingdom - Occupational Exposure Limits	
WEL TWA (OEL TWA)	5 mg/m³
WEL STEL (OEL STEL)	10 mg/m³

DNEL and PNEC

Phosphorodithioic acid, mixed O,O-bis(iso-bu and pentyl) esters, zinc salts (68784-31-6)	
DNEL/DMEL (Workers)	
Acute - systemic effects, dermal	100 mg/kg bodyweight/day
Acute - systemic effects, inhalation	496.4 mg/m³
Long-term - systemic effects, dermal	10.42 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	2.93 mg/m³
DNEL/DMEL (General population)	
Acute - systemic effects, dermal	50 mg/kg bodyweight/day
Acute - systemic effects, inhalation	198.6 mg/m³
Acute - systemic effects, oral	29 mg/kg bodyweight/day
Long-term - systemic effects,oral	0.21 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	11.75 mg/m³
Long-term - systemic effects, dermal	2.1 mg/kg bodyweight/day
PNEC (Water)	
PNEC aqua (freshwater)	4 µg/l
PNEC aqua (marine water)	4.6 µg/l
PNEC aqua (intermittent, freshwater)	44 µg/l
PNEC (Sediment)	
PNEC sediment (freshwater)	0.0701 mg/kg dwt
PNEC sediment (marine water)	0.00701 mg/kg dwt

Blending Quality, Value & Service since 1921
Head Office
WITHAM OIL & PAINT (SOHAM) LTD
Regal Drive
Soham
Cambs CB7 5BE
01353 723373
WITHAM OIL & PAINT LTD
Outer Circle Road
Lincoln
LN2 4HL
01522 521192
WITHAM MOTORSPORT LTD
Regal Drive
Soham
Cambs CB7 5BE
01353 723373
withamgroup.co.uk
ISO 9001 Quality Management Systems CERTIFIED FM37897
ISO 14001 Environmental Management CERTIFIED EMS727531
Qualube THE QUALITY LUBRICANT
Woco THE QUALITY PAINT
03/23

QUALUBE ENDURASYN SS 10W30

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Phosphorodithioic acid, mixed O,O-bis(iso-bu and pentyl) esters, zinc salts (68784-31-6)	
PNEC (Soil)	
PNEC soil	0.0548 mg/kg dwt
PNEC (Oral)	
PNEC oral (secondary poisoning)	8.33 mg/kg food
PNEC (STP)	
PNEC sewage treatment plant	3.8 mg/l

8.2. Exposure controls

Appropriate engineering controls

Appropriate engineering controls:
Ensure good ventilation of the work station.

Personal protection equipment

Personal protective equipment symbol(s):



Eye and face protection

Eye protection:
Safety glasses

Eye protection			
Type	**Field of application**	**Characteristics**	**Standard**
Safety glasses	Droplet	Plastic	EN 166

Skin protection

Skin and body protection:
Wear suitable protective clothing

Blending Quality, Value & Service since 1921

Head Office

WITHAM OIL & PAINT (SOHAM) LTD
Regal Drive
Soham
Cambs CB7 5BE
01353 723373

WITHAM OIL & PAINT LTD
Outer Circle Road
Lincoln
LN2 4HL
01522 521192

WITHAM MOTORSPORT LTD
Regal Drive
Soham
Cambs CB7 5BE
01353 723373

withamgroup.co.uk

bsi ISO 9001 Quality Management Systems CERTIFIED FM37897 ISO 14001 Environmental Management CERTIFIED EMS727531

Qualube THE QUALITY LUBRICANT
Woco THE QUALITY PAINT

03/23

QUALUBE ENDURASYN SS 10W30

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Skin and body protection	
Type	**Standard**
Tyvek® Gown/Coveralls	

Hand protection:
Protective gloves

Hand protection					
Type	**Material**	**Permeation**	**Thickness (mm)**	**Penetration**	**Standard**
Disposable gloves	Nitrile rubber (NBR)	3 (> 60 minutes)		2 (< 1.5)	EN 388

Respiratory protection

Respiratory protection:
In case of insufficient ventilation, wear suitable respiratory equipment

Respiratory protection			
Device	**Filter type**	**Condition**	**Standard**
Aerosol mask	Filter A2/B2	Long term exposure	EN 132

Environmental exposure controls

Environmental exposure controls:
Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	:	Liquid
Colour	:	brown.
Appearance	:	Viscous liquid.
Odour	:	slight.
Odour threshold	:	Not available
Melting point	:	Not applicable
Freezing point	:	Not available
Boiling point	:	Not available

Blending Quality, Value & Service since 1921
Head Office
WITHAM OIL & PAINT (SOHAM) LTD
Regal Drive
Soham
Cambs CB7 5BE
01353 723373
WITHAM OIL & PAINT LTD
Outer Circle Road
Lincoln
LN2 4HL
01522 521192
WITHAM MOTORSPORT LTD
Regal Drive
Soham
Cambs CB7 5BE
01353 723373
withamgroup.co.uk
bsi ISO 9001 Quality Management Systems CERTIFIED FM37897 ISO 14001 Environmental Management CERTIFIED EMS727531
Qualube THE QUALITY LUBRICANT
Woco THE QUALITY PAINT
03/23

QUALUBE ENDURASYN SS 10W30

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Flammability	:	Not applicable
Lower explosion limit	:	Not available
Upper explosion limit	:	Not available
Flash point	:	> 200 °C Pensky-Martens closed cup.
Auto-ignition temperature	:	Not available
Decomposition temperature	:	Not available
pH	:	Not available
Viscosity, kinematic	:	9.3 – 12.5 Cst @ 100 Deg C
Solubility	:	Material insoluble in water.
Partition coefficient n-octanol/water (Log Kow)	:	Not available
Vapour pressure	:	< 0.1 mm Hg
Vapour pressure at 50°C	:	Not available
Density	:	Not available
Relative density	:	Not available
Relative vapour density at 20°C	:	Not available
Particle characteristics	:	Not applicable

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

No additional information available

Blending Quality, Value & Service since 1921

Head Office

WITHAM OIL & PAINT (SOHAM) LTD
Regal Drive
Soham
Cambs CB7 5BE
01353 723373

WITHAM OIL & PAINT LTD
Outer Circle Road
Lincoln
LN2 4HL
01522 521192

WITHAM MOTORSPORT LTD
Regal Drive
Soham
Cambs CB7 5BE
01353 723373

withamgroup.co.uk

bsi ISO 9001 Quality Management Systems CERTIFIED FM37897 ISO 14001 Environmental Management CERTIFIED EMS727531

Qualube THE QUALITY LUBRICANT
Woco THE QUALITY PAINT

03/23

QUALUBE ENDURASYN SS 10W30

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Phosphorodithioic acid, mixed O,O-bis(iso-bu and pentyl) esters, zinc salts (68784-31-6)	
LD50 dermal rabbit	> 5000 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)

Skin corrosion/irritation : Not classified

Phosphorodithioic acid, mixed O,O-bis(iso-bu and pentyl) esters, zinc salts (68784-31-6)	
pH	≈ 7 Temp.: 25 °C Concentration: (≈)0,00116 other: Remarks on result: 'other:'

Serious eye damage/irritation : Not classified

Phosphorodithioic acid, mixed O,O-bis(iso-bu and pentyl) esters, zinc salts (68784-31-6)	
pH	≈ 7 Temp.: 25 °C Concentration: (≈)0,00116 other: Remarks on result: 'other:'

Respiratory or skin sensitisation : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified.
Reproductive toxicity : Not classified
STOT-single exposure : Not classified
STOT-repeated exposure : Not classified

Phosphorodithioic acid, mixed O,O-bis(iso-bu and pentyl) esters, zinc salts (68784-31-6)	
NOAEL (oral, rat, 90 days)	125 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity Study in Rodents)

Aspiration hazard : Not classified

QUALUBE ENDURASYN SS 10W30	
Viscosity, kinematic	9.3 – 12.5 Cst @ 100 Deg C

Blending Quality, Value & Service since 1921
Head Office
WITHAM OIL & PAINT (SOHAM) LTD
Regal Drive
Soham
Cambs CB7 5BE
01353 723373
WITHAM OIL & PAINT LTD
Outer Circle Road
Lincoln
LN2 4HL
01522 521192
WITHAM MOTORSPORT LTD
Regal Drive
Soham
Cambs CB7 5BE
01353 723373
withamgroup.co.uk
bsi ISO 9001 Quality Management Systems CERTIFIED FM37897 ISO 14001 Environmental Management CERTIFIED EMS727531
Qualube THE QUALITY LUBRICANT
Woco THE QUALITY PAINT
03/23

QUALUBE ENDURASYN SS 10W30

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

HIGHLY REFINED MINERAL OIL MIXTURE(C15-C50)	
Viscosity, kinematic	9000 mm²/s

DISTILLATES(PETROLEUM) HYDROTREATED HEAVY PARAFFINIC (64742-54-7)	
Viscosity, kinematic	30 mm²/s 40 deg c

11.2. Information on other hazards

No additional information available

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.

Hazardous to the aquatic environment, short–term (acute) : Not classified

Hazardous to the aquatic environment, long–term (chronic) : Not classified

Phosphorodithioic acid, mixed O,O-bis(iso-bu and pentyl) esters, zinc salts (68784-31-6)	
LC50 - Fish [1]	46 mg/l Test organisms (species): Cyprinodon variegatus

12.2. Persistence and degradability

QUALUBE ENDURASYN SS 10W30	
Persistence and degradability	Not rapidly degradable

Highly Refined mineral oil(C15-C50)	
Persistence and degradability	Not rapidly degradable

Phosphorodithioic acid, mixed O,O-bis(iso-bu and pentyl) esters, zinc salts (68784-31-6)	
Persistence and degradability	Not rapidly degradable

Blending Quality, Value & Service since 1921

Head Office

WITHAM OIL & PAINT (SOHAM) LTD
Regal Drive
Soham
Cambs CB7 5BE
01353 723373

WITHAM OIL & PAINT LTD
Outer Circle Road
Lincoln
LN2 4HL
01522 521192

WITHAM MOTORSPORT LTD
Regal Drive
Soham
Cambs CB7 5BE
01353 723373

withamgroup.co.uk

bsi ISO 9001 Quality Management Systems CERTIFIED FM37897 ISO 14001 Environmental Management CERTIFIED EMS727531

Qualube THE QUALITY LUBRICANT
Woco THE QUALITY PAINT

03/23

QUALUBE ENDURASYN SS 10W30

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Benzenesulfonic acid methyl-,mono-C20-26-branched alkyl derivs., calcium salts (722503-69-7)	
Persistence and degradability	Not rapidly degradable

Benzenesulfonic acid methyl1-,mono-C20-24-branched alkyl derivs.,calcium salts (722503-68-6)	
Persistence and degradability	Not rapidly degradable

HIGHLY REFINED MINERAL OIL MIXTURE(C15-C50)	
Persistence and degradability	Not rapidly degradable

NON CLASSIFIED COMPONENT	
Persistence and degradability	Not rapidly degradable

DISTILLATES(PETROLEUM) HYDROTREATED HEAVY PARAFFINIC (64742-54-7)	
Persistence and degradability	Not rapidly degradable

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

QUALUBE ENDURASYN SS 10W30
This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII
This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

No additional information available

Blending Quality, Value & Service since 1921

Head Office

WITHAM OIL & PAINT (SOHAM) LTD
Regal Drive
Soham
Cambs CB7 5BE
01353 723373

WITHAM OIL & PAINT LTD
Outer Circle Road
Lincoln
LN2 4HL
01522 521192

WITHAM MOTORSPORT LTD
Regal Drive
Soham
Cambs CB7 5BE
01353 723373

withamgroup.co.uk

bsi ISO 9001 Quality Management Systems CERTIFIED FM37897 ISO 14001 Environmental Management CERTIFIED EMS727531

Qualube THE QUALITY LUBRICANT
Woco THE QUALITY PAINT

03/23

QUALUBE ENDURASYN SS 10W30

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional waste regulation	:	Disposal must be done according to official regulations.
Waste treatment methods	:	Dispose of contents/container in accordance with licensed collector's sorting instructions.
Product/Packaging disposal recommendations	:	Dispose in a safe manner in accordance with local/national regulations. a licensed hazardous-waste disposal contractor or collection site except for empty clean containers which can be disposed of as non-hazardous waste.
European List of Waste (LoW, EC 2000/532)	:	13 02 05* - mineral-based non-chlorinated engine, gear and lubricating oils
HP Code	:	HP7 - "Carcinogenic:" waste which induces cancer or increases its incidence

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number or ID number				
Not regulated for transport				
14.2. UN proper shipping name				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.3. Transport hazard class(es)				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.4. Packing group				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.5. Environmental hazards				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
No supplementary information available				

14.6. Special precautions for user

Overland transport

Not regulated

Blending Quality, Value & Service since 1921

Head Office

WITHAM OIL & PAINT (SOHAM) LTD
Regal Drive
Soham
Cambs CB7 5BE
01353 723373

WITHAM OIL & PAINT LTD
Outer Circle Road
Lincoln
LN2 4HL
01522 521192

WITHAM MOTORSPORT LTD
Regal Drive
Soham
Cambs CB7 5BE
01353 723373

withamgroup.co.uk

bsi ISO 9001 Quality Management Systems CERTIFIED FM37897 ISO 14001 Environmental Management CERTIFIED EMS727531

Qualube THE QUALITY LUBRICANT
Woco THE QUALITY PAINT

03/23

QUALUBE ENDURASYN SS 10W30

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Transport by sea
Not regulated

Air transport
Not regulated

Inland waterway transport
Not regulated

Rail transport
Not regulated

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU-Regulations

REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

Blending Quality, Value & Service since 1921

Head Office

WITHAM OIL & PAINT (SOHAM) LTD
Regal Drive
Soham
Cambs CB7 5BE
01353 723373

WITHAM OIL & PAINT LTD
Outer Circle Road
Lincoln
LN2 4HL
01522 521192

WITHAM MOTORSPORT LTD
Regal Drive
Soham
Cambs CB7 5BE
01353 723373

withamgroup.co.uk

bsi ISO 9001 Quality Management Systems CERTIFIED FM37897 ISO 14001 Environmental Management CERTIFIED EMS727531

Qualube THE QUALITY LUBRICANT
Woco THE QUALITY PAINT

03/23

QUALUBE ENDURASYN SS 10W30

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Dual-Use Regulation (428/2009)

Contains no substance subject to the COUNCIL REGULATION (EC) No 428/2009 of 5 May 2009 setting up a Community regime for the control of exports, transfer, brokering and transit of dual-use items.

Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Indication of changes		
Section	**Changed item**	**Comments**
	Supersedes version of	**Added**
	Revision date	**Added**
1.1	UFI on SDS 1.1	**Added**

Abbreviations and acronyms:	
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
COD	Chemical oxygen demand (COD)
DMEL	Derived Minimal Effect level

Blending Quality, Value & Service since 1921

Head Office

WITHAM OIL & PAINT (SOHAM) LTD
Regal Drive
Soham
Cambs CB7 5BE
01353 723373

WITHAM OIL & PAINT LTD
Outer Circle Road
Lincoln
LN2 4HL
01522 521192

WITHAM MOTORSPORT LTD
Regal Drive
Soham
Cambs CB7 5BE
01353 723373

withamgroup.co.uk

bsi ISO 9001 Quality Management Systems CERTIFIED FM37897 ISO 14001 Environmental Management CERTIFIED EMS727531

Qualube THE QUALITY LUBRICANT
Woco THE QUALITY PAINT

03/23

QUALUBE ENDURASYN SS 10W30

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Abbreviations and acronyms:	
DNEL	Derived-No Effect Level
EC-No.	European Community number
EC50	Median effective concentration
EN	European Standard
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
VOC	Volatile Organic Compounds
CAS-No.	Chemical Abstract Service number
N.O.S.	Not Otherwise Specified

Blending Quality, Value & Service since 1921

Head Office

WITHAM OIL & PAINT (SOHAM) LTD
Regal Drive
Soham
Cambs CB7 5BE
01353 723373

WITHAM OIL & PAINT LTD
Outer Circle Road
Lincoln
LN2 4HL
01522 521192

WITHAM MOTORSPORT LTD
Regal Drive
Soham
Cambs CB7 5BE
01353 723373

withamgroup.co.uk

bsi ISO 9001 Quality Management Systems CERTIFIED FM37897 ISO 14001 Environmental Management CERTIFIED EMS727531

Qualube THE QUALITY LUBRICANT
Woco THE QUALITY PAINT

03/23

QUALUBE ENDURASYN SS 10W30

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Abbreviations and acronyms:	
vPvB	Very Persistent and Very Bioaccumulative
ED	Endocrine disruptor

Other information : Technical Manager.

Full text of H- and EUH-statements:	
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2
Aquatic Chronic 4	Hazardous to the aquatic environment – Chronic Hazard, Category 4
Asp. Tox. 1	Aspiration hazard, Category 1
Carc. 1B	Carcinogenicity, Category 1B
EUH208	Contains Benzenesulfonic acid methyl-,mono-C20-26-branched alkyl derivs, calcium salts (722503-69-7) (21139), Benzenesulfonic acid methyl1-,mono-C20-24-branched alkyl derivs,calcium salts (722503-68-6) (21138). May produce an allergic reaction.
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
H304	May be fatal if swallowed and enters airways.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H350	May cause cancer.
H411	Toxic to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.
Skin Sens. 1B	Skin sensitisation, category 1B

The classification complies with : ATP 12

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

Blending Quality, Value & Service since 1921

Head Office

WITHAM OIL & PAINT (SOHAM) LTD
Regal Drive
Soham
Cambs CB7 5BE
01353 723373

WITHAM OIL & PAINT LTD
Outer Circle Road
Lincoln
LN2 4HL
01522 521192

WITHAM MOTORSPORT LTD
Regal Drive
Soham
Cambs CB7 5BE
01353 723373

withamgroup.co.uk

bsi ISO 9001 Quality Management Systems CERTIFIED FM37897 ISO 14001 Environmental Management CERTIFIED EMS727531

Qualube THE QUALITY LUBRICANT
Woco THE QUALITY PAINT

03/23